


ENGLISH



ALUMINUM TREKKING POLES

USING AND ADJUSTING THE QUICK-LOCK MECHANISM


Prior to every use, check that all locks are tight to avoid slippage.




1. Open Quick Locks fully (until the lever stops) and adjust poles to desired height.



2. Turn thumb screw $\frac{1}{4}$ - $\frac{1}{2}$ of a turn clockwise to tighten.



3. Close the Quick-Lock – if tightened correctly, the lock should require firm pressure to close.



4. Test the lock by applying downward pressure on the pole, ensuring the sections do not collapse/slip. If the sections collapse/slip repeat the steps above.

ACCESSORIES – TIPS AND BASKETS

Your CMT trekking poles came with a set of sand/mud, snow baskets and two sets of tips – boot tips and small rubber tips (see website for suggested use). The baskets can be put onto the trekking poles by screwing onto the pole tip threads in a clockwise direction. To remove the baskets, unscrew in a counter-clockwise direction. The two sets of rubber tips can be put onto the trekking pole by pushing and wiggling the tips until they are on securely. When removing the rubber tips the first time it may require you to pull the tips off with pliers.

REGULAR INSPECTION AND CARE

Before and after each use, it is the user's responsibility to read instructions, understand how to properly use, check to see that the adjustment mechanisms open and close smoothly and are adjusted/tightened/tensioned properly.

- Make sure the poles are not damaged, cracked or broken
- Never put oil or silicon on the pole shafts. This could cause the pole sections to slip during use
- Should the poles get wet, lengthen the lower shafts and allow them to dry completely before storage

Any modification to the pole or its parts voids the warranty. CMT warrants for one year from purchase date and only to the original retail buyer that our products are free from defects in material and workmanship. We do not warranty for misuse or unintended purposes (skiing, tent poles or bending the poles beyond normal tolerances).

For any additional questions or to obtain replacement parts, visit our website at www.cascademountaintech.com or call **855-873-5765**.

Thank you for your purchase!